

SPECIFICATIONS

CIO-DAC08-I

CIO-DAC16-I

Analog Current Outputs



**MEASUREMENT
COMPUTING™**

Revision 3, October, 2000

© Copyright 2000, MEASUREMENT COMPUTING CORPORATION

Power Consumption

CIO-DAC16-I	
+5V supply	320 mA typical, 500 mA max
+12V supply	150 mA typical, 190 mA max
-12V supply	100 mA typical, 130 mA max
CIO-DAC08-I	
+5V supply	320 mA typical, 500 mA max
+12V supply	75 mA typical, 100 mA max
-12V supply	50 mA typical, 65 mA max

Analog Output

D/A type	AD7237
Resolution	12 bits
Number of channels	
CIO-DAC16-I	16 Current Outputs
CIO-DAC08-I	8 Current Outputs
Output Range	4 to 20mA
Voltage compliance	6 to 36V
D/A pacing	Software paced
Data transfer	Software
Offset error	Adjustable to zero
Gain error	Adjustable to zero
Differential nonlinearity	±1 LSB max
Integral nonlinearity	±1 LSB max
Monotonicity	Guaranteed monotonic to 15 bits over temperature
Gain drift (DAC)	±15 ppm/°C max
Bipolar offset drift (DAC)	±5 ppm/°C max
Unipolar offset drift (DAC)	±3 ppm/°C max
Throughput	System dependant
Settling time (Full scale step to .01%)	12 µs typ, 19 µs max
Miscellaneous	Double buffered output latches DAC output state on power up and reset undefined

Environmental

Operating temperature range	0 to 70°C
Storage temperature range	-40 to 100°C
Humidity	0 to 90% non-condensing

Measurement Computing Corporation
10 Commerce Way
Suite 1008
Norton, Massachusetts 02766
(508) 946-5100
Fax: (508) 946-9500
E-mail: info@mccdaq.com
www.mccdaq.com