

# **SPECIFICATIONS**

**CIO-DI48  
CIO-DI96  
CIO-DI192**

**Digital Inputs**



Revision 3, October, 2000

© Copyright 2000, MEASUREMENT COMPUTING CORPORATION

**Typical for 25°C unless otherwise specified.**

## **Power consumption**

+5V quiescent	
CIO-DI48	300 mA typical, 390 mA maximum
CIO-DI96	475 mA typical, 620 mA maximum
CIO-DI192	630 mA typical, 820 mA maximum

## **Digital Inputs**

Digital Type	74LS373
Configuration	Input only
CIO-DI48	6 banks of 8 bits
CIO-DI96	12 banks of 8 bits
CIO-DI192	24 banks of 8 bits
Number of channels	
CIO-DI48	48 inputs
CIO-DI96	96 inputs
CIO-DI192	192 inputs
Input High	2.0 volts min, 7 volts absolute maximum
Input Low	0.8 volts max, -0.5 volts absolute minimum
Miscellaneous	Locations provided for installation of pull-up or pull-down resistors.

## **Environmental**

Operating temperature range	0 to 70°C
Storage temperature range	-40 to 100°C
Humidity	0 to 90% non-condensing

**Measurement Computing Corporation  
10 Commerce Way  
Suite 1008  
Norton, Massachusetts 02766  
(508) 946-5100  
Fax: (508) 946-9500  
E-mail: [info@mccdaq.com](mailto:info@mccdaq.com)  
[www.mccdaq.com](http://www.mccdaq.com)**