

Isolated Digital I/O Modules

for DBK208 & DBK210



OPTO-22® Modules for DBK208

A wide selection of OPTO-22® or compatible modules (NEMA ICS 2-230-.02) are available to switch AC or DC loads and to sense AC or DC voltages.

OPTO-22® Switching Modules

Module	AC Control			DC Control		Dry-Contact
	PCAC1-W	PCAC2-W	PCAC3-W	PCDC1-W	PCDC2-W	PCDC3-W
Operating voltage	24-140 VAC	24-280 VAC	24-280 VAC	5-60 VDC	5-200 VDC	0-100 VDC 0-130 VAC
Nominal line voltage	120 VAC	240 VAC	120-240 VAC	60 VDC max	200 VDC max	100 VDC max 130 VAC max
Isolation	4000V RMS	4000V RMS	4000V RMS	4000V RMS	4000V RMS	1500 VDC
Current rating @ 45°C	3A	3A	3A	3A	1A	1.5A max
Turn-on time	1/2 cycle 0 voltage	1/2 cycle 0 voltage	1/2 cycle 0 voltage	100 µs	100 µs	750 µs
Turn-off time	1/2 cycle 0 current	1/2 cycle 0 current	1/2 cycle 0 current	750 µs	750 µs	750 µs
Contact mode	normally open	normally open	normally open	normally open	normally open	normally open

OPTO-22® Sensing Modules

Module	AC Sensing		DC Sensing	
	PSAC1-W	PSAC3-W	PSDC1-W	PSDC2-W
Input voltage range	10-32 VAC	90-140 VAC	2.5-28 VDC	4-16 VDC
Input current @ max line	25 mA	11 mA	30 mA	45 mA
Input allowed for output	1 mA 3V	3 mA 45V	0.2 mA 1V	0.7 mA 1V
Turn-on time	5 msec	20 msec	1 msec	0.05 msec
Turn-off time	5 msec	20 msec	1.5 msec	0.1 msec

Grayhill 70M Series for DBK210

A wide selection of Grayhill 70M Series modules are available to switch or sense a large range of AC or DC voltages.

70M Series Switching Modules

Module	AC Control		DC Control	
	PCAC1-70M	PCDC1-70M	PCAC1-70M	PCDC1-70M
Operating voltage	24-140 VAC	3-60 VDC	24-140 VAC	3-60 VDC
Nominal line voltage	120 VAC	60 VDC	120 VAC	60 VDC
Isolation	4000V RMS	4000V RMS	4000V RMS	4000V RMS
Current rating @ 45°C	3A	3A	3A	3A
Turn-on time	8.3 msec	20 µs	8.3 msec	20 µs
Turn-off time	8.3 msec	50 µs	8.3 msec	50 µs

70M Series Sensing Modules

Module	AC or DC Sensing		DC Sensing	
	PSAC1-70M	PSAC3-70M	PSDC1-70M	PSDC2-70M
Input voltage range	12-32 VAC 10-32 VDC	90-140 VAC/DC	3-32 VDC	3-32 VDC
Input current @ max line	18 mA	8 mA	18 mA	18 mA
Turn-on time	5 msec	20 msec	0.2 msec	0.2 msec
Turn-off time	5 msec	20 msec	0.4 msec	0.4 msec

Ordering Information


OPTO-22® Modules

Description	Part No.
AC control module	PCAC1-W
12 to 140 VAC (normally open)	PCAC2-W
AC control module	PCAC3-W
24 to 280 VAC (normally open)	PCDC1-W
AC control module	PCDC2-W
24 to 280 VAC (normally closed)	PCDC3-W
DC control module	PSAC1-W
5 to 60 VDC (normally open)	PSAC3-W
DC control module	PSDC1-W
5 to 200 VDC (normally open)	PSDC2-W
AC/DC control module	PSAC1-70M
0 to 100 VDC, 0 to 130 VAC (normally open)	PSAC3-70M
AC/DC input module	PSDC1-70M
12 to 32 VAC/DC	PSDC2-70M
AC/DC input module	PSAC1-70M
90 to 140 VAC/DC	PSAC3-70M
DC input module 2.4 to 28 VDC	PSDC1-W
DC input module 4 to 15 VDC	PSDC2-W

Grayhill 70M Series Modules

AC control module 120 VAC	PCAC1-70M
DC control module 3-60 VDC	PCDC1-70M
DC input module 3-32 VDC	PSDC1-70M
AC/DC input module	PSAC1-70M
12-32 VAC/10-32 VDC	PSAC3-70M
AC input module 120 VAC	PSAC1-70M

Note: OPTO-22® and Grayhill 70M modules must be purchased separately. All sales are final with no right of return.



Grayhill 70M Series digital I/O modules feature a narrow footprint allowing for high-channel density configurations