

# PCI-DAS1200/JR

## Specifications



**MEASUREMENT  
COMPUTING™**

Document Revision 3.2, February, 2010  
© Copyright 2010, Measurement Computing Corporation

# Specifications

Typical for 25 °C unless otherwise specified.

Specifications in *italic text* are guaranteed by design.

## Analog input

Table 1. Analog input specifications

Parameter	Specification
<i>A/D converter type</i>	7800
Resolution	12 bits
Number of channels	8 differential or 16 single-ended, software selectable
Input ranges	Bipolar: $\pm 10\text{ V}$ , $\pm 5\text{ V}$ , $\pm 2.5\text{ V}$ , $\pm 1.25\text{ V}$ Unipolar: $0\text{ to }10\text{ V}$ , $0\text{ to }5\text{ V}$ , $0\text{ to }2.5\text{ V}$ , $0\text{ to }1.25\text{ V}$ Software selectable
A/D pacing	Programmable: internal counter or external source (A/D External Pacer) or software polled
Burst mode	Software selectable option, burst rate = $3\ \mu\text{s}$
A/D trigger sources	External digital: A/D External Trigger
A/D triggering modes	External digital: Software enabled, rising edge, hardware trigger Pre-trigger: Unlimited pre- and post-trigger samples. Total # of samples must be $> 512$ .
Data transfer	From 1024 sample FIFO via REPINSW, interrupt or software polled
<i>A/D conversion time</i>	$3\ \mu\text{s}$
Throughput	330 kHz min
Relative accuracy	$\pm 1.5\text{ LSB}$
Differential linearity error	$\pm 0.75\text{ LSB}$
Integral linearity error	$\pm 0.5\text{ LSB typ}$ , $\pm 1.5\text{ LSB max}$
Gain error (relative to calibration reference)	$\pm 0.02\%$ of reading max
<i>No missing codes guaranteed</i>	$12\text{ bits}$
<i>Gain drift (A/D specs)</i>	$\pm 6\text{ ppm}/^\circ\text{C}$
<i>Zero drift (A/D specs)</i>	$\pm 1\text{ ppm}/^\circ\text{C}$
Common mode range	$\pm 10\text{ V}$
CMRR @ 60 Hz	70 dB
<i>Input leakage current</i>	$200\text{ nA}$
<i>Input impedance</i>	$10\text{ MOhm, min}$
<i>Absolute maximum input voltage</i>	$\pm 35\text{ V}$
Noise distribution:	Rate = 1-330 KHz, average % $\pm 2$ bins, average % $\pm 1$ bin, average # bins ▪ All ranges: $100\% / 100\% / 3\text{ bins}$

## Digital input/output

Table 2. DIO specifications

Parameter	Specification
Digital type	82C55A
Configuration	2 banks of 8, 2 banks of 4, programmable by bank as input or output
Number of I/O	24 (FIRSTPORTA 0 through FIRSTPORTC 7)
Output high	3.0 volts @ -2.5 mA min
Output low	0.4 volts @ 2.5 mA max
Input high	2.0 volts min, Vcc+0.5 volts absolute max
Input low	0.8 volts max, GND-0.5 volts absolute min
Power-up / reset state	Input mode (high impedance)
Interrupts	INTA# - mapped to IRQn via PCI BIOS at boot-time
Interrupt enable	Programmable
Interrupt sources	Residual counter, End-of-channel-scan, AD-FIFO-not-empty, AD-FIFO-half-full

## Counter section

Table 3. Counter specifications

Parameter	Specification
Counter type	82C54
Configuration	Two 82C54 devices. 3 down counters per 82C54, 16 bits each
82C54A:	
Counter 0 - ADC residual sample counter.	<ul style="list-style-type: none"> <li>▪ Source: ADC Clock.</li> <li>▪ Gate: Internal programmable source.</li> <li>▪ Output: End-of-Acquisition interrupt.</li> </ul>
Counter 1 - ADC pacer lower divider	<ul style="list-style-type: none"> <li>▪ Source: 10 MHz oscillator</li> <li>▪ Gate: tied to counter 2 gate, programmable source.</li> <li>▪ Output: chained to counter 2 clock.</li> </ul>
Counter 2 - ADC pacer upper divider	<ul style="list-style-type: none"> <li>▪ Source: counter 1 output.</li> <li>▪ Gate: Tied to counter 1 gate, programmable source.</li> <li>▪ Output: ADC pacer clock (if software selected), available at user connector.</li> </ul>
82C54B:	
Counter 0 - pretrigger mode	<ul style="list-style-type: none"> <li>▪ Source: ADC clock</li> <li>▪ Gate: external trigger</li> <li>▪ Output: End-of-Acquisition interrupt</li> </ul>
Counter 0 - user counter 4 (when in non-pretrigger mode)	<ul style="list-style-type: none"> <li>▪ Source: User input at 100-pin connector (CLK4) or internal 10 MHz (software selectable)</li> <li>▪ Gate: user input at 100-pin connector (GATE4)</li> <li>▪ Output: available at 100-pin connector (OUT4)</li> </ul>
Counter 1 - user counter 5	<ul style="list-style-type: none"> <li>▪ Source: user input at 100-pin connector (CLK5)</li> <li>▪ Gate: user input at 100-pin connector (GATE5)</li> <li>▪ Output: available at 100-pin connector (OUT5)</li> </ul>
Counter 2 - user counter 6	<ul style="list-style-type: none"> <li>▪ Source: user input at 100-pin connector (CLK6)</li> <li>▪ Gate: user input at 100-pin connector (GATE6)</li> <li>▪ Output: available at 100-pin connector (OUT6)</li> </ul>
Clock input frequency	10 MHz max
High pulse width (clock input)	30 ns min
Low pulse width (clock input)	50 ns min
Gate width high	50 ns min
Gate width low	50 ns min
Input low voltage	0.8 V max

Parameter	Specification
<i>Input high voltage</i>	2.0 V min
<i>Output low voltage</i>	0.4 V max
<i>Output high voltage</i>	3.0 V min

## Power consumption

Table 4. Power consumption specifications

Parameter	Specification
+5 V operating (A/D converting to FIFO)	0.8 A typical, 1.0 A max

## Environmental

Table 5. Environmental specifications

Parameter	Specification
<i>Operating temperature range</i>	0 to 70 °C
<i>Storage temperature range</i>	-40 to 100 °C
<i>Humidity</i>	0 to 90% non-condensing

## Main connector and pin out

Table 6. I/O connector specifications

Connector type	100-pin high density
Compatible cable	C100FF-x, unshielded ribbon cable. x = length in feet
Compatible accessory products (with C100FF-x cable)	ISO-RACK16/P CIO-ERB08 (DADP-5037 adaptor and TN-MC78M05CT voltage regulator required *) CIO-ERB24 (DADP-5037 adaptor required *) CIO-SERB24 (DADP-5037 adaptor required) SSR-RACK08 (DADP-5037 adaptor required *) SSR-RACK24 (DADP-5037 adaptor required *) BNC-16SE BNC-16DI CIO-MINI50 (2 required) CIO-TERM100 (1 required) SCB-50 (1 required)  * Details on the DADP-5037 adaptor board are available on our web site at <a href="http://www.mccdaq.com/cbicalog/cbiproduct.asp?dept_id=103&amp;pf_id=1381">www.mccdaq.com/cbicalog/cbiproduct.asp?dept_id=103&amp;pf_id=1381</a>

### 8-channel differential mode pin out

Pin	Signal Name	Pin	Signal Name
1	LLGND	51	FIRSTPORTA Bit 0
2	CH0 IN HI	52	FIRSTPORTA Bit 1
3	CH0 IN LO	53	FIRSTPORTA Bit 2
4	CH1 IN HI	54	FIRSTPORTA Bit 3
5	CH1 IN LO	55	FIRSTPORTA Bit 4
6	CH2 IN HI	56	FIRSTPORTA Bit 5
7	CH2 IN LO	57	FIRSTPORTA Bit 6
8	CH3 IN HI	58	FIRSTPORTA Bit 7
9	CH3 IN LO	59	FIRSTPORTB Bit 0
10	CH4 IN HI	60	FIRSTPORTB Bit 1
11	CH4 IN LO	61	FIRSTPORTB Bit 2
12	CH5 IN HI	62	FIRSTPORTB Bit 3
13	CH5 IN LO	63	FIRSTPORTB Bit 4
14	CH6 IN HI	64	FIRSTPORTB Bit 5
15	CH6 IN LO	65	FIRSTPORTB Bit 6
16	CH7 IN HI	66	FIRSTPORTB Bit 7
17	CH7 IN LO	67	FIRSTPORTC Bit 0
18	LLGND	68	FIRSTPORTC Bit 1
19	N/C	69	FIRSTPORTC Bit 2
20	N/C	70	FIRSTPORTC Bit 3
21	N/C	71	FIRSTPORTC Bit 4
22	N/C	72	FIRSTPORTC Bit 5
23	N/C	73	FIRSTPORTC Bit 6
24	N/C	74	FIRSTPORTC Bit 7
25	N/C	75	N/C
26	N/C	76	N/C
27	N/C	77	N/C
28	N/C	78	N/C
29	N/C	79	N/C
30	N/C	80	CTR6 CLK
31	N/C	81	CTR6 GATE
32	N/C	82	CTR6 OUT
33	N/C	83	N/C
34	N/C	84	N/C
35	N/C	85	CTR5 CLK
36	N/C	86	CTR5 GATE
37	N/C	87	CTR5 OUT
38	N/C	88	N/C
39	CTR4 CLK	89	GND
40	CTR4 GATE	90	+12V
41	CTR4 OUT	91	GND
42	A/D EXTERNAL PACER	92	-12V
43	N/C	93	N/C
44	N/C	94	N/C
45	A/D EXTERNAL TRIGGER IN	95	A/D INTERNAL PACER OUTPUT
46	N/C	96	N/C
47	N/C	97	N/C
48	PC +5V	98	N/C
49	N/C	99	N/C
50	GND	100	GND

**16-channel single-ended mode pin out**

Pin	Signal Name	Pin	Signal Name
1	LLGND	51	FIRSTPORTA Bit 0
2	CH0 IN	52	FIRSTPORTA Bit 1
3	CH8 IN	53	FIRSTPORTA Bit 2
4	CH1 IN	54	FIRSTPORTA Bit 3
5	CH9 IN	55	FIRSTPORTA Bit 4
6	CH2 IN	56	FIRSTPORTA Bit 5
7	CH10 IN	57	FIRSTPORTA Bit 6
8	CH3 IN	58	FIRSTPORTA Bit 7
9	CH11 IN	59	FIRSTPORTB Bit 0
10	CH4 IN	60	FIRSTPORTB Bit 1
11	CH12 IN	61	FIRSTPORTB Bit 2
12	CH5 IN	62	FIRSTPORTB Bit 3
13	CH13 IN	63	FIRSTPORTB Bit 4
14	CH6 IN	64	FIRSTPORTB Bit 5
15	CH14 IN	65	FIRSTPORTB Bit 6
16	CH7 IN	66	FIRSTPORTB Bit 7
17	CH15 IN	67	FIRSTPORTC Bit 0
18	LLGND	68	FIRSTPORTC Bit 1
19	N/C	69	FIRSTPORTC Bit 2
20	N/C	70	FIRSTPORTC Bit 3
21	N/C	71	FIRSTPORTC Bit 4
22	N/C	72	FIRSTPORTC Bit 5
23	N/C	73	FIRSTPORTC Bit 6
24	N/C	74	FIRSTPORTC Bit 7
25	N/C	75	N/C
26	N/C	76	N/C
27	N/C	77	N/C
28	N/C	78	N/C
29	N/C	79	N/C
30	N/C	80	CTR6 CLK
31	N/C	81	CTR6 GATE
32	N/C	82	CTR6 OUT
33	N/C	83	N/C
34	N/C	84	N/C
35	N/C	85	CTR5 CLK
36	N/C	86	CTR5 GATE
37	N/C	87	CTR5 OUT
38	N/C	88	N/C
39	CTR4 CLK	89	GND
40	CTR4 GATE	90	+12V
41	CTR4 OUT	91	GND
42	A/D EXTERNAL PACER	92	-12V
43	N/C	93	N/C
44	N/C	94	N/C
45	A/D EXTERNAL TRIGGER IN	95	A/D INTERNAL PACER OUTPUT
46	N/C	96	N/C
47	N/C	97	N/C
48	PC +5V	98	N/C
49	N/C	99	N/C
50	GND	100	GND

**Measurement Computing Corporation**  
**10 Commerce Way**  
**Suite 1008**  
**Norton, Massachusetts 02766**  
**(508) 946-5100**  
**Fax: (508) 946-9500**  
**E-mail: [info@mccdaq.com](mailto:info@mccdaq.com)**  
**[www.mccdaq.com](http://www.mccdaq.com)**