

PCM-COM Series

RS-232, 422 and 485 Interfaces for PC-CARD / PCMCIA Compatible Computers

PCM-COM232



Features

- RS-232 serial port
- Uses 16550 UART
- 5, 6, 7, or 8 data bits
- odd, even or no parity
- 115 KBaud data rates

Specifications

| | |
|----------------|--|
| Serial ports | 1 |
| Configured as | COM1, COM2, COM3 or COM4 |
| Max. baud rate | 56KB as COMn: port 115 KB with custom SW |
| Serial modes | 5, 6, 7, or 8 data bits odd, even or no parity 0, 1 or 2 stop bits |
| UART | 16550 |

Form Factor

PCMCIA type II compliant

Software Description

Fully compatible with your computers built-in serial port control software.

Board Configurations & Cables

PCM-COM232 includes the PCM-C232-12I, 12 inch cable. For additional cables please order the PCM-C232-12I **\$25.00**

| | |
|------------------|----------------|
| PCM-COM232 | \$99.00 |
|------------------|----------------|

PCM-COM485 & PCM-COM422



Features

- RS-422 or 485 serial ports
- Uses 16550 UART
- 5, 6, 7, or 8 data bits
- odd, even or no parity
- 115 KBaud data rates

Specifications

| | |
|----------------|--|
| Serial ports | 1 |
| Configured as | COM1, 2, 3 or 4 or COM4 |
| Max. baud rate | 56KB as COMn: port 115 KB with custom SW |
| Serial modes | 5, 6, 7, or 8 data bits odd, even or no parity 0, 1 or 2 stop bits |
| Output control | (RS-485 only) Software selectable transmitter allows networked operation |
| UART | 16550 |
| Cable length | 1.2 Kilometer (422 & 485) |
| Network nodes | Up to 32 (RS-485 only) |

Form Factor

PCMCIA type II compliant

Software Description

Compatible with your computers built-in serial port control software.

Board Configurations & Cables

PCM-COM485 single port RS-485 interface. Use PCM-C485/485 cable

PCM-COM422 provides a single port of either RS-232 or RS-422. For RS-232 use PCM-C422/232 cable, for RS-422 use PCM-C422/422 cable

| | |
|------------------|-----------------|
| PCM-COM485 | \$149.00 |
| PCM-COM422 | \$149.00 |

PCM-C232-12I



PCM-C232-12I **\$25.00**

Description

Brings RS-232 serial communication signals out to standard DB9

For Use with:

PCM-COM232 (one cable is included with the card.)

PCM-C422/422



PCM-C422/422 **\$25.00**

Description

Brings RS-422 serial communication signals out to standard DB9

For Use with:

PCM-COM422

PCM-C422/232



PCM-C422/232 **\$25.00**

Description

Brings RS-232 serial communication signals out to standard DB9

For Use with:

PCM-COM422

PCM-C485/485



PCM-C485/485 **\$25.00**

Description

Brings RS-485 serial communication signals out to standard DB9

For Use with:

PCM-COM485