

USB-501-LT

Specifications



**MEASUREMENT
COMPUTING™**

Revision 1.2, October, 2009
© Copyright 2009, Measurement Computing Corporation

Specifications

All specifications are subject to change without notice.

Typical for 25 °C unless otherwise specified.

Specifications in *italic text* are guaranteed by design.

Temperature

Table 1. Temperature specifications

Parameter	Specification
Measurement range	-10 °C (+14 °F) minimum, +50 °C (+122 °F) maximum
Resolution	+1 °C (+2 °F) typical
Accuracy (overall error)	±2.5 °C (±4.5 °F) maximum

Sampling

Table 2. Sampling specifications

Parameter	Specification
Sampling intervals	15 min, 30 min, 1 h, 2 h
Max temperature samples	4,080
Units	°C or °F

Alarms

Table 3. Alarm conditions

Parameter	Specification
High temp alarm range	-10 °C (+14 °F) minimum, 79.5 °C (175 °F) maximum
Low temp alarm range	-10 °C (+14 °F) minimum, 79.5 °C (175 °F) maximum
Temp resolution	0.5 °C (1 °F)

USB specifications

Table 4. USB specifications

USB device type	USB 2.0 (full-speed)
Device compatibility	USB 1.1, USB 2.0

Power

Table 5. Power specifications

CR1620 lithium button cell life	@30 min logging rate	1 month minimum
---------------------------------	----------------------	-----------------

Environmental

Table 6. Environmental specifications

Operating temperature range	-10 °C (+14 °F) minimum, 50 °C (122 °F) maximum
-----------------------------	---

LED flashing modes

Table 7. LED functions

Parameter	Condition	Specification
Green LED	Flashes once	Currently logging, no alarm
Red LED	Flashes once	Currently logging, low alarm condition *
	Flashes twice	Currently logging, high alarm condition *
No LEDs flash		Logger stopped or battery depleted

*If both alarms have Hold selected, the LED indicator only applies to the first alarm condition detected.

Mechanical

Table 8. Mechanical specifications

Dimensions	68 mm long x 18 mm wide x 9.4 mm high (2.7 in. long x 0.7 in. wide x 0.4 in. high)
------------	--

Measurement Computing Corporation
10 Commerce Way
Suite 1008
Norton, Massachusetts 02766
(508) 946-5100
Fax: (508) 946-9500
E-mail: info@mccdaq.com
www.mccdaq.com