

Features

- Provide auxiliary power for expanding IOtech's data acquisition systems
- Install into a DBK10, DBK41, or DBK60 expansion enclosure

The DBK32A provides auxiliary power to meet certain configurations (see calculating your power needs). The DBK32A provides IOtech's data acquisition systems with additional power (± 15 VDC at 500 mA) in system configurations where the number of expansion cards exceeds the built-in power capacity.

The DBK32A can be installed directly into a DBK10, DBK41, or DBK60 expansion enclosure. Each is compatible with all DBK cards and is powered via an included AC adapter, a DBK30A battery/excitation module, a DBK34A battery/UPS module, or any 9 to 18 VDC source.




The DBK32A provides additional power for LogBook and Daq systems when the power expansion needs exceed the built-in capacity of the mainframe

Specifications

- Line Regulation: 0.5%
- Load Regulation: 1.0%
- Total Output Power: 16 VA full load
- Input Voltage Range: 9 to 18 VDC
- Included AC Adapter: 15 VDC @ 3.33A
- Full Load Input Current Range: 1.05A @ 18 VDC, 2.10A @ 9 VDC
- Full Load Efficiency: 80%
- Parallel Provision: OR-ing diodes on output lines allow use of multiple DBK32A's in larger systems
- Controls: ON/OFF rocker arm switch
- Indicators: LED driven by input voltage
- Over-Voltage Protection: Fuse followed by 19V zener clamp
- Switching Frequency: 100 kHz min
- Environment: -20 to 70 °C
- Input Fuse: 3A
- Dimensions: 209 mm W x 19 mm D x 82 mm H (8.25" x 0.75" x 3.25")
- Connector: DB37 male, mates with P1 and supplies power to other DBK cards; input power accepted via DIN5
- Isolation Input-to-Output: 500 VDC
- Output Voltages:
 - +15 VDC nominal @ 535 mA
 - 15 VDC nominal @ 535 mA

Auxiliary Power Supply Card Block Diagram



Ordering Information

Description
Auxiliary power supply card with AC adapter

Part No.
DBK32A

Product Compatibility

- ✓ LogBook
- ✓ DaqBook

Cables

5-pin male DIN to 5-pin male DIN, 6 in. CA-115
For use with DBK10, use CA-37-x ribbon cable, or contact factory of additional cabling options
For use with DBK60 or LogBook/360, no cable is required (except from DBK60 or LogBook/360 to the A/D mainframe)
For use with no enclosure, use CA-37-x where x is the number of DBK devices attached
For use with DaqLab Series (internal slots), use CA-255-2T with one board, or CA-37-2 for use with two DBK cards (or contact factory for additional cabling options)